



Lexmark XC4352

Security and performance



Lexmark XC4352

The Lexmark XC4352 is designed for performance, security, and ease of use for mid-to-large workgroups at speeds up to 52 ppm*. Single-pass two-sided scanning, ultrasonic multifeed detection, and a 10-inch (25 cm) tablet-like touchscreen make handling your print jobs easy. Toner cartridges that yield up to 26,000/15,000 black/color pages** keep you going.

Made to last. Easy to upgrade.

- ▶ With durable steel frames, long-life components and high-yield cartridges, printers are intentionally engineered to last seven years or more.
- ▶ Long-lasting Unison™ Toner delivers consistently outstanding print quality, reduces internal wear on long-life components, and protects the print system.
- ▶ Easily upgradable to the latest apps and security features.



Faster performance and ease of use

- ▶ Scanning is fast and accurate thanks to the single-pass two-sided automatic document feeder with ultrasonic multifeed detection.
- ▶ The large, tablet-like, button-free touchscreen will help you intuitively complete every task, from the basic to the complex.
- ▶ An Intelligent Storage Drive (ISD) is standard on this model, providing faster startup, faster data retrieval and more reliability.

Make a statement with professional color

Enjoy the benefits of vibrant, professional-quality output allowing you to do more color printing in-house—saves time and money. Match corporate colors on marketing collateral and brand-sensitive text and graphics with PANTONE® calibration and Lexmark Named Color Replacement.

Secure by design

Lexmark security features help keep your information safe—in the document, on the device, over the network and at all points in between. Our comprehensive approach to product security is a design and engineering mandate across our entire product portfolio.

Sustainability matters

- ▶ Designed for the circular economy.
- ▶ Automatic two-sided printing is standard, along with built-in energy-saving modes that help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- ▶ The award-winning Lexmark Cartridge Collection Program (LCCP) and Lexmark Equipment Collection Program (LECP) minimize waste and support recycling (availability varies by country).

Power up with IoT

- ▶ Sophisticated, IoT-enabled printers are loaded with sensors that continuously monitor hundreds of data points.
- ▶ When you connect your device to Lexmark Cloud Services, you can optimize performance and uptime with additional features like predictive service and automatic supplies replenishment.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

** Average yield based on approximately 5% print coverage. In demonstration of circular economy principles, genuine Lexmark supplies with Unison™ Toner may contain components recovered from the Lexmark Cartridge Collection Program (LCCP).

Lexmark XC4352



- 1 **Multifunction product with 10-inch (25 cm) touch screen**
24.44 x 18.85 x 20.9 in.
621 x 479 x 533 mm
- 2 **550-Sheet tray with 100-sheet multipurpose feeder**
Dimensions included as part of base model
- 3 **550-Sheet Tray**
4.7 x 18.23 x 19 in.
119 x 463 x 483 mm
- 4 **550-Sheet Tray**
4.7 x 18.23 x 19 in.
119 x 463 x 483 mm

- 5 **550-Sheet Tray**
4.7 x 18.23 x 19 in.
119 x 463 x 483 mm
- 6 **550-Sheet Tray**
4.7 x 18.23 x 19 in.
119 x 463 x 483 mm
- 7 **Adjustable Stand**
20.5 x 25.7 x 24.6 in.
521 x 653 x 625 mm
- 8 **Convenience Stapler LV**
3.23 x 4.29 x 4.77 in.

- Standard
- Optional

P/N
47C9900

Hardware
Lexmark XC4352

P/N
24B7515

Supplies
Lexmark XC4342, 4352 Cyan
14.2K Toner Cartridge

24B7516

Lexmark XC4342, 4352 Magenta
14.2K Toner Cartridge

24B7517

Lexmark XC4342, 4352 Yellow
14.2K Toner Cartridge

24B7518

Lexmark XC4342, 4352 Black 25K
Toner Cartridge

24B7557

Lexmark XC4352 Cyan 15K Toner
Cartridge

24B7558

Lexmark XC4352 Magenta 15K
Toner Cartridge

24B7559

Lexmark XC4352 Yellow 15K
Toner Cartridge

24B7560

Lexmark XC4352 Black 26K Toner
Cartridge

71C0W00

Lexmark CS/CX730, 735, C/
XC4342, C/4352 170K Waste
Container

71C0Z10

Lexmark CS/CX730, 735, C/
XC4342, C/XC4352 Black 150K
Imaging Unit

71C0Z50

Lexmark CS/CX730, 735, C/
XC4342, C/XC4352 Color (CMY)
150K Imaging Unit

P/N

Paper Handling

40C2100

550-Sheet Tray

47C4500

Convenience Stapler

P/N

Memory Options

27X0400

500+ GB Hard Disk

57X0070

Removable Hard Disk Enclosure
Kit

P/N

Application Solutions

57X0300

Contact Authentication Device

57X0301

Contactless Authentication
Device

82S1203

IPDS License

82S1204

Bar Code License

P/N

Connectivity

1021294

USB Cable (2-meter)

27X0823

MarkNet N8370 Wireless for
CS720, CS725, CX725

27X6410

Lexmark MarkNet N8372 802.11
a/b/g/n/ac Wireless Print Server

57X7020

English Keyboard Kit

SPD0001

Surge Protective Device,
110-120V

P/N

Furniture

40C2300

Adjustable Stand

Supports up to four optional 550-sheet trays.

All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at http://www.lexmark.com/publications/furniture_safety/

Product Specifications

Lexmark XC4352

Printing

Display	Lexmark e-Task 10-inch (25 cm) class color touch screen
Print Speed	Up to: Black: 52 ppm ¹ (Letter) / Color: 52 ppm ¹ (Letter)
Time to First Page	As fast as: Black: 5.6 seconds / Color: 6.1 seconds
Print Resolution	Black: 1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi) / Color: 4800 CQ (2400 x 600 dpi), 1200 x 1200 dpi
Memory	Standard: 2048 MB / Maximum: 2048 MB
Hard Disk	Intelligent Storage Drive included; Magnetic Hard Disk available
Recommended Monthly Page Volume	2000 - 20000 pages ²
Maximum Monthly Duty Cycle	Up to: 150000 pages per month ³

Copying

Copy Speed	Up to: Black: 52 cpm ¹ (Letter) / Color: 52 cpm ¹ (Letter)
Time to First Copy	As fast as: Black: 5.7 seconds / Color: 6.3 seconds

Scanning

Scanner Type / ADF Scan	Flatbed scanner with ADF / DADF (single pass Duplex)
A4/Ltr Duplex Scan Speed	Up to: Black: 98 / 104 sides per minute / Color: 98 / 104 sides per minute
A4/Ltr Simplex Scan Speed	Up to: Black: 49 / 52 sides per minute / Color: 49 / 52 sides per minute
ADF Paper Input Capacity	Up to: 100 pages 20 lb or 75 gsm bond

Faxing

Modem Speed	ITU T.30, V.34 Half-Duplex, 33.6 Kbps
-------------	---------------------------------------

Supplies⁴

Laser Cartridge Yields	up to: 14,200 ⁵ -page Color (CMY) High Yield Cartridges / up to: 25,000 ⁵ -page Black Extra High Yield Cartridge / up to: 15,000 ⁵ -page Color (CMY) High Yield Cartridges / up to: 26,000 ⁵ -page Black Extra High Yield Cartridge
Imaging Unit Estimated Yield	Up to: 150000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage ⁶
Cartridge(s) Shipping with Product	5,000 ⁵ -page Black and Color (CMYK) Return Program Toner Cartridges

Paper Handling

Included Paper Handling	100-Sheet Multipurpose Feeder, Integrated Duplex, 300-Sheet Output Bin, 550-Sheet Input
Optional Paper Handling	550-Sheet Tray
Paper Input Capacity	Up to: Standard: 650 pages 20 lb or 75 gsm bond / Maximum: 2850 pages 20 lb or 75 gsm bond
Paper Output Capacity	Up to: Standard: 300 pages 20 lb or 75 gsm bond / Maximum: 300 pages 20 lb or 75 gsm bond
Media Types Supported	Vinyl Labels, Banner Paper, Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide
Media Sizes Supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope

General Information⁷

Standard Ports	Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear Hi-Speed USB Port Compatible with USB 2.0 Specification (Type A), USB 2.0 Specification Hi-Speed Certified (Type B), One Internal Card Slot
Optional Network Ports	Internal MarkNet N8370 802.11b/g/n/a Wireless, NFC
Noise Level	Operating: 53 dBA (Print) / 56 dBA (Copy) / 51 dBA (Scan)
Specified Operating Environment	Humidity: 8 to 80% Relative Humidity / Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2896 Meters (9,500 Feet)
Limited Warranty	See Statement of Limited Warranty: 1-Year Onsite Service, Next Business Day
Size / Weight	H x W x D: 24.44 x 18.85 x 20.9 in. / 87.08 lb.
ENERGY STAR Typical Electricity Consumption	TEC: 0.69 kilowatt-hours per week

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.
² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average yield based on approximately 5% print coverage. Yield stated on cartridge labels, packaging, and printer device menu pages may be substantially lower than final ISO tested yield. For Lexmark's official statement of yield, see ISO yield reports at https://www.lexmark.com/en_us/products/supplies-and-accessories/iso-page-yields/color-laser-reports.html. Update firmware on your device to ensure accuracy of displayed yield. ⁶ Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁷ Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2022 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries and regions. MOPRIA®, the Mopria® Logo, and the Mopria Alliance™ word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT is a trademark of the Green Electronics Council in the United States and other countries. PANTONE® is the property of Pantone LLC. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/> (<http://www.openssl.org/>)).



lexmark.com